QuietGue® Pro Acoustical Glue




The High Performing, Low Cost Noise Reducing Glue

QuietGlue® Pro is a high performance, low cost acoustical compound designed to be cost effective for commercial projects and small do-it-yourself projects.

QuietGlue® Pro Benefits:

- Easy to use
- Ideal for use with virtually any kind of wood or drywall
- Does not require special training
- Low VOC, water-based compound, solvent-free
- Lab tested in accordance with ASTM D3273 and E90

STOP THE NOISE IN 2 EASY STEPS




Visit www.QuietRock.com for installation instructions and complete documentation.

Product Specifications:

Model:	QuietGlue® Pro
Color:	Orange
Density:	1,030 kg/m
Solid content:	>70 wt %
Viscosity:	400,000 - 800,000 centipoise
Drying time:	24-48 hours
Coverage:	16 sqft/tube; 73 sqft/gallon
Storage temp:	40° F - 100° F (Do Not Freeze)
Working time:	15 minutes
Available sizes*:	28-oz tube, 1-gal pail, 5-gal pail,
	case of 12 28-oz tubes

* Tubes require a standard caulking gun. A bulk caulking gun is recommended for use with the 1 gallon and 5 gallon buckets.

QuietGlue[®] Pro Performance





PABCO® Gypsum | 37851 Cherry Street, Newark, CA 94560 | 1.800.797.8159 | www.PabcoGypsum.com | www.QuietRock.com | PN: 101-00054-042914 © 2014 PABCO® Gypsum. All rights reserved. PABCO® Gypsum, the PABCO® logo, EZ-SNAP™, Quiet®, QuietRock®, QuietPutty®, QuietSeal® Pro, QuietSeam®, QuietGue® Pro, and QuietCoat® are trademarks or registered trademarks of Pacific Coast Building Products, Inc. and licensed to PABCO® Gypsum in the United States and other countries. Information subject to change without notice.